





## LED Canopy Light – 100W

## Model: TL-C100-A


Surface mount LED canopy lights are suitable for both outdoor and indoor commercial applications such as loading docks, petrol stations, freezers, cool rooms, food processing plants and common areas.

## **Product Features**

- Only consumes 100w of power
- Aluminium die cast housing
- Daylight & Microwave Motion Sensor
- Long operating life and performance
- 120° Beam Angle
- IP65 Waterproof housing









## SPECIFICATION

SPECIFICATION	
Colour	Cool White (5000K)
Lumen (Im)	14,000lm
LED Efficiency (Lm/w)	>140lm/w
Light Source	SMD LED's
CRI (%)	>80%
Beam Angle	120°
Power Requirement	AC 220~240V 50Hz
Power Consumption	100W
Housing	Die Cast Aluminium
Lifespan	> 40,000 hours
Operation Temperature	-20°C~+40°C
Dimension (mm)	420 ( L ) × 420 ( W ) x 67 (D)
Weight	4.5kg
Sensor (option by remote)	Daylight & Microwave Motion Sensor
Warranty	5 years

Tallis Lighting & Energy Solutions Pty Ltd. 1/13 Commerce Circuit, Yatala Qld 4207 Phone: 1300 494 995 Website: www.tallislighting.com.au Email: info@tallislighting.com.au