

LED Down Light– 4W

Model: TL-DL-4W-CCT

LED Downlights are suitable for supermarkets, office buildings, business halls, shopping malls, hotels, and coffee shops. They can also be used for residential lighting, particularly in living rooms, activity rooms, and bedrooms.

Product Features

- Longevity Type
- Aluminium die cast housing
- Less heat emission
- Full range power input 200-240 VAC
- 105 x 467 mm
- 100° Beam Angle
- IP40



SPECIFICATION

Colour	(3000-4000-5000K) CCT
Lumen (lm)	480Lm
Efficiency (Lm/w)	>120lm/w
Light Source	SMD 2835
CRI (%)	>80%
Beam Angle	100°
Power Requirement	AC 220~240 V
Power Consumption	4W
Housing	Die Cast Aluminium & Plastic
Lifespan	> 30,000 hours
Operation Temperature	-20°C~+50°C
Dimension (mm)	105 × 46 mm (90mm cut out)
PF	0.89-0.92
Protection Rating	IP40
Warranty	2 years

Tallis Lighting & Energy Solutions Pty Ltd. 1/13 Commerce Circuit, Yatala Qld 4207

Phone: 1300 494 995

Website: www.tallislighting.com.au

Email: info@tallislighting.com.au